

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd PO Box 1556 • Toowong 4066 • Phone: 1300 396 275 • Fax: 1300 360 440
www.dymark.com.au



Dy-Mark PROTECH® Freeze Spray



Dy-Mark PROTECH® Freeze Spray is an efficient cooling system that instantly freezes surfaces to -50 degrees C. Its powerful blast of propellant instantly chills suspect electrical and electronic components. It is non-flammable, plastic safe, leaves no residue and is non-abrasive. Is also ideal for removing chewing-gum or sweets from fabrics.

DIRECTIONS FOR USE

Recommended Uses:

Thermostats, computers, thermometers, circuit boards, laboratory and precision electronic equipment, office equipment and more uses.

DO NOT SPRAY ON SKIN. Can will dispense freezing liquid which can cause frostbite on exposed skin. Shake can well.

Application:

Spray can in UPRIGHT position only. Spray onto surface from a distance of 10-15cms. Spray in short bursts. Use extension tube for hard to reach areas.

TECHNICAL DATA

Size:	300g Aerosol
Colour:	Clear
Consistency:	Colourless Liquid
Propellant:	HFC134 A (1,1,1,2 - Tetra fluoroethane)

STORAGE

Store below 50C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents under pressure. Do not puncture or incinerate, even when empty.

SAFETY INFORMATION

NON FLAMMABLE

Ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye Contact: Rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.