



Dy-Mark PROTECH® Dry PTFE Lubricant



Dy-Mark PROTECH® Dry PTFE Lubricant is a multi-purpose dry film lubricant. It will penetrate and bond to metal, wood, rubber and most surfaces and will form a non-staining micro thin film that prevents sticking, reducing friction and wear. It will seal out moisture, inhibit corrosion and resists oil, dust and dirt build up. Will not melt, freeze or wash off.

DIRECTIONS FOR USE

Recommended Uses:

Hinges, chains, window tracks, locks, conveyers, cutting blades, saw blades, sliding drawers, sliding doors, and other uses.

Application:

Shake can for at least 45 seconds AFTER the mixing ball begins to rattle. Shake can occasionally during use. Clean and dry surface area thoroughly. Spray can in UPRIGHT position only. Spray light even film directly onto surfaces.

Leave film to dry minimum 10-15 minutes. Full cure in 24 hours. Repeat application when needed for long term dry film lubrication and protection, allowing it to dry between applications.

TECHNICAL DATA

Size:	150g Aerosol
Colour:	Clear
Consistency:	Dry Film
Propellant:	DME

STORAGE

Store below 50C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents under pressure. Do not puncture or incinerate, even when empty.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye Contact: Rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.