

LABELMATE USA

Label Handling Innovations

Powered Label Unwinders UCAT-40 / UCAT-3



UCAT-40
The "Ultimate Unwinder"

Eliminate stress on your printer by feeding labels with a Powered Unwinder, and use larger supply rolls for greater economy.

Powered Unwinders operate at speeds up to 30-inches per second.
(Powered Unwinders can also rewind.)

An Inner Flange is included with all Unwinders. Outer Flanges are optional.

CORE DIA.	LABEL WIDTH	ROLL DIA.	THE "ULTIMATE UNWINDER"	MODEL	ADD SUFFIX
3"	Up to 6" (152-mm)	Up to 16" (400-mm)	With a 6" wide (152-mm) "Quick-Chuck" Core Holder. Continuously adjustable feed rate. A Sensor Arm starts & stops the unwinding automatically.	UCAT-40	-CHUCK
	Up to 8.6" (220-mm)		With an 8.6" wide (220-mm) "Quick-Chuck" .		-CHUCK-220
	Up to 10" (254-mm)		With a 10" wide (254-mm) "Quick-Chuck" .		-CHUCK-10



UCAT-3-STANDARD



UCAT-3-ACH



UCAT-3-CHUCK

CORE DIA.	LABEL WIDTH	ROLL DIA.	POWERED HEAVY-DUTY UNWINDERS	MODEL	ADD SUFFIX
1" to 4"		Up to 11" (280-mm)	With a 1" to 4" Adjustable Core Holder . (If Outer Flange is desired, use APG-CAT)	UCAT-3	-ACH
3"	Up to 6" (152-mm)	Up to 12" (305-mm)	With a 6" wide Fin-Style Core Holder . Continuously adjustable feed rate. Sensor Arm starts & stops unwinding automatically.		-STANDARD
			With a 6" wide "Quick-Chuck" .		-CHUCK
	Up to 8.6" (220-mm)		With an 8.6" wide "Quick-Chuck" .		-CHUCK-220
	Up to 10" (254-mm)		With a 10" wide Fin-Style Core Holder .		-W10
			With a 10" wide "Quick-Chuck" .		-CHUCK-10